762/B8
CROCHET MACHINE

For narrow tapes and decorative trims, with yarn creel and beam stands.



762/B8 machine overview

Equipped with four beam stands and a meter counter.

30 inches	1,400 rpm	260
Working width	Machine speed	Yarn creel positions

Ningbo Yishuo Machinery & Electron Co., Ltd.
nbyishuo.com | lloyd.jiang@nbyishuo.com

01 / MACHINE CONFIGURATION

Technical specifications

Main machine dimensions, needle gauges and equipment configuration.

762/B8 CROCHET MACHINE	
Model	**762/B8**
Main machine size (L × W × H)	**1,650 × 700 × 1,750 mm**
Working width	**30 inches**
Needle gauges (needles per inch)	**12 / 14 / 15 / 18 / 20 / 22**
Machine speed	**1,400 rpm**
Yarn creel	**260 positions**
Beam stands	**4**
Meter counter	**Included**

MACHINE DETAILS



Knitting area detail



Side view and yarn supply arrangement

02 / PRODUCT REFERENCE

Tape samples & width reference

Decorative tape samples and width / strip-count combinations.



Tape samples

Decorative crochet tapes

A selection of narrow tape and trim constructions.

Tape width	Number of strips
6 mm	**90**
8 mm	**75**
15 mm	**38**
20 mm	**28**
25 mm	**24**
40 mm	**15**
60 mm	**10**
80 mm	**8**

Select the machine setup to suit the required tape width and construction.