EQUIPMENT & MATERIALS

YS-FD106 Shoelace Waxing and Polishing Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Speed	6-10 m/min
Motor	2 1/4 HP, three-phase
Heater power	2.4 kW
Current rating	17 A
Machine dimensions	2,510 x 850 x 1,785 mm

CONFIGURATION

Automatic temperature control / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FS/2S1 Finishing and Starching Machine - 600 mm rollers

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	600x1500 mm
Rollers	2
Baths	1
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FS/2S2 Finishing and Starching Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	600x1500 mm
Rollers	2
Baths	2
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FS/2H Finishing and Starching Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	600x1500 mm
Rollers	2
Baths	1
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FS/6 Finishing and Starching Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	780x800 mm
Rollers	6
Baths	1
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-TFS/8 Finishing and Starching Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	780x800 mm
Rollers	8
Baths	1
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FS/12TM Finishing and Starching Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	780x800 mm
Rollers	12
Baths	1
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FS/L1 Finishing and Starching Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Roller dimensions	780x800 mm
Rollers	1
Baths	1
Motor	4 HP
Tape paths	1-6
Line speed	30 m/min per strip
Heating options	Electric / natural gas / CNG / steam

CONFIGURATION

Automatic temperature control / Variable frequency control / Adjustable tension

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YS-LX08 Pre-shrinking Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Machine dimensions	7,000 x 2,500 x 2,600 mm
Power	10 kW
Power supply	AC 380 V
Temperature	60-120 C
Working width	450 mm
Heating options	Oil / steam / electric
Control	PLC
Net weight	900 kg

CONFIGURATION

PLC control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com