EQUIPMENT & MATERIALS

YSY-2/300 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	2
Reed width	300 mm
Heald frames	14
Pattern cycle	8-48
Motor	2 HP
Speed	200 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-2/200 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	2
Reed width	200 mm
Heald frames	14
Pattern cycle	8-48
Motor	2 HP
Speed	350 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-2/165 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	2
Reed width	165 mm
Heald frames	14
Pattern cycle	8-48
Motor	2 HP
Speed	500 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-4/130 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	4
Reed width	130 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	800 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-4/80 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	4
Reed width	80 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-8/35 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heald frames	15
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-8/30 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heald frames	15
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-10/25 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heald frames	15
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-12/20 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Reed width	20 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-1/500 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	1
Reed width	500 mm
Heald frames	14
Pattern cycle	8-40
Motor	2 HP
Speed	200 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-10/45 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	10
Reed width	45 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-10/30 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	10
Reed width	30 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-8/55 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	8
Reed width	55 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-6/80 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	6
Reed width	80 mm
Heald frames	16
Pattern cycle	8-48
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-6/65 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	6
Reed width	65 mm
Heald frames	16
Pattern cycle	8-40
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-S-12/30 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	12
Reed width	30 mm
Heald frames	14
Pattern cycle	8-40
Motor	1.5 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-6/55 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	6
Reed width	55 mm
Heald frames	20
Pattern cycle	8-40
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-8/35 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	8
Reed width	35 mm
Heald frames	20
Pattern cycle	8-48
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-10/30 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Reed width	30 mm
Heald frames	20
Pattern cycle	8-48
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-12/20 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Reed width	20 mm
Heald frames	20
Pattern cycle	8-48
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-4/65 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	4
Reed width	65 mm
Heald frames	20
Pattern cycle	8-48
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-6/42 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	6
Reed width	42 mm
Heald frames	20
Pattern cycle	8-40
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-D-8/27 Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	8
Reed width	27 mm
Heald frames	20
Pattern cycle	8-48
Motor	2 HP
Speed	1400 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-Z-10/30 Zipper Tape Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	10
Reed width	30 mm
Heald frames	12
Pattern cycle	8
Motor	1.5 HP
Speed	1700 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-Z-12/30 Zipper Tape Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	12
Reed width	30 mm
Heald frames	12
Pattern cycle	8
Motor	1.5 HP
Speed	1700 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSY-Z-14/20 Zipper Tape Needle Loom

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Heads	14
Reed width	20 mm
Heald frames	20
Pattern cycle	8-48
Motor	2 HP
Speed	1700 rpm
Weft density	3.5-36.7 picks/cm

CONFIGURATION

Yarn-break stop / Automatic circulating lubrication

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com