EQUIPMENT & MATERIALS

Cord Take-up Winder

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Equipment type	Cord Takeup Winder

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSH-SW62 Sewing Thread Winder

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Spindles	6
Bobbins per spindle	1 or 2
Package shapes	Cone, column, horn/bugle
Bobbin size	Cone / horn: 4, 5, 6 in; column: 2 in
Thread length	0-30,000 m
Power supply	3-phase / 380 V / 50 Hz; customizable
Packing dimensions	2.15 x 0.80 x 1.07 m
Net / gross weight	450 / 500 kg

CONFIGURATION

Independent spindle control / Electronic length counter / Silicone oil device / Electronic tension control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSH-SWH42 Sewing Thread Winder

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Configuration	4 spindles / 2 bobbins each
Bobbin size	4 in
Package diameter	115 mm
Winding speed	900-1,000 m/min
Pattern-back setting	3-4
Power	1.5 kW
Machine dimensions	2.00 x 0.88 x 1.50 m
Net / gross weight	500 / 600 kg

CONFIGURATION

Independent spindle control / Electronic length counter / Silicone oil device / Electronic tension control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-B626 Computerized Bobbin Winder - 32 spindles

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Spindles	32
Construction	Double-sided
Twist direction	S or Z
Yarn package weight	750 g
Package forming	Computer controlled
Power	3.55 kW

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-B626 Computerized Bobbin Winder - 48 spindles

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Spindles	48
Construction	Double-sided
Twist direction	S or Z
Yarn package weight	750 g
Package forming	Computer controlled
Power	3.55 kW

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-B626 Computerized Bobbin Winder - 64 spindles

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Spindles	64
Construction	Double-sided
Twist direction	S or Z
Yarn package weight	750 g
Package forming	Computer controlled
Power	3.55 kW

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-B626 Computerized Bobbin Winder - 96 spindles

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Spindles	96
Construction	Double-sided
Twist direction	S or Z
Yarn package weight	750 g
Package forming	Computer controlled
Power	3.55 kW

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YS-LD01 Automatic Yarn Rewinding Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Winding mode	Soft winding
Heads	6 per section
Grooved drum	OD 82 mm; pitch 2.5; symmetric 0 degrees
Traverse length	147 mm / 6 in
Power	100 W per head
Power supply	3-phase 440 V, 50/60 Hz

CONFIGURATION

Independent head control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YS-LD02 Automatic Yarn Rewinding Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Winding mode	Hard winding
Heads	6 per section
Grooved drum	OD 82 mm; pitch 2.5; symmetric 0 degrees
Traverse length	147 mm / 6 in
Power	100 W per head
Power supply	3-phase 440 V, 50/60 Hz

CONFIGURATION

Independent head control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSF-H01 Ribbon Rolling Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Roll diameter	350 mm
Tape width	8-50 mm
Speed	110 m/min
Motor	1 HP + inverter
Control	Digital counter; automatic stop

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSF-H02 Ribbon Rolling Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Roll diameter	350 mm
Tape width	8-50 mm
Speed	110 m/min
Motor	1 HP
Control	Manual counter

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSF-H03 Ribbon Rolling Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Roll diameter	350 mm
Tape width	8-50 mm
Speed	110 m/min
Motor	1 HP
Control	Automatic counter; speed control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-FT Vertical Tape Winding Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Tape width	2-15 cm
Speed	100 m/min
Power	2 kW

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com