EQUIPMENT & MATERIALS

YSL-S302 Warping Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Yarn creel	192
Motor	2 HP
Line speed	Up to 600 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Yarn-break stop / Electronic length counter / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-S303 Warping Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Yarn creel	256
Motor	2 HP
Line speed	Up to 600 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Yarn-break stop / Electronic length counter / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-S304 Warping Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Yarn creel	300
Motor	2 HP
Line speed	Up to 600 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Yarn-break stop / Electronic length counter / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-SA60 Elastic Yarn Warping Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Yarn creel	60
Main motor	2 HP
Rubber-frame motor	2 HP
Line speed	Up to 400 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Adjustable tension / Electronic length counter / Yarn-break stop / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-SA80 Elastic Yarn Warping Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Yarn creel	80
Main motor	2 HP
Rubber-frame motor	2 HP
Line speed	Up to 400 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Adjustable tension / Electronic length counter / Yarn-break stop / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-SA120 Elastic Yarn Warping Machine

Series reference image. Refer to the selected configuration below.



TECHNICAL SPECIFICATIONS

Yarn creel	120
Main motor	2 HP
Rubber-frame motor	1.5 + 1.5 HP
Line speed	Up to 400 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Adjustable tension / Electronic length counter / Yarn-break stop / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

YSL-D300 Double-head Warping Machine

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Yarn creel	300
Motor	2 HP x 2
Line speed	600 m/min
Beam diameter	400 mm
Beam inner length	300 mm

CONFIGURATION

Yarn-break stop / Electronic length counter / Variable frequency control

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com

EQUIPMENT & MATERIALS

Sample Warping Machine - 12 ends

Product configuration and technical specifications.



TECHNICAL SPECIFICATIONS

Motor	0.75 kW / 220 V
Maximum ends	12 ends
Machine dimensions	1,600 x 620 x 900 mm
Creel dimensions	600 x 600 x 900 mm
Net weight	150 kg

CONFIGURATION

PLC control / Automatic stop

Working output depends on material and configuration. Confirm the final specification with Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com