CORD FINISHING / TIPPING EQUIPMENT

1730 Automatic Shoelace Tipping Machine

Automatic shoelace film tipping and cutting, with a 35-150 cm cutting length range. PLC control is available as an option.



1730 machine overview

TECHNICAL DATA

Cutting length	35-150 cm
Reference output	5,000-6,000 pcs/h
Net weight	750 kg
Standard supply	3-phase, 380 V, 50 Hz
Motor power	1.1 kW (3-phase 380 V)
Electric heater	220 V / 300 W
Mould thickness	6 mm
Tooling diameters	2.3 / 2.5 / 2.8 / 3.0 / 3.2 / 3.5 / 3.8 / 4.0 / 4.2 / 4.5 / 5.0 mm
Film width	25 / 30 / 35 / 40 mm

CONFIGURATION

- One set of 6 mm knife moulds
- One shoelace film feeding plate
- Optional PLC control

Output depends on the cord, film and tip setup. PLC control is optional. Confirm the final configuration with Yishuo.

PLAN YOUR CONFIGURATION

Send your cord sample, material, cutting length and required tip size to Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com