CORD FINISHING / TIPPING EQUIPMENT

2530 Automatic Shoelace Tipping Machine

Automatic film tipping and cutting for shoelaces, with a 32-250 cm cutting length range. PLC control is available as an option.



2530 machine overview

TECHNICAL DATA

Cutting length	32-250 cm
Reference output	4,500-5,000 pcs/h
Net weight	850 kg
Standard supply	3-phase, 380 V, 50 Hz
Motor power	1.1 kW (3-phase 380 V)
Electric heater	220 V / 300 W
Mould thickness	6 mm
Tooling diameters	2.3 / 2.5 / 2.8 / 3.0 / 3.2 / 3.5 / 3.8 / 4.0 / 4.2 / 4.5 / 5.0 mm
Film width	25 / 30 / 35 / 40 mm

CONFIGURATION

- One set of 6 mm knife moulds
- One shoelace film feeding plate
- Optional PLC control

Output depends on the cord, film and tip setup. PLC control is optional. Confirm the final configuration with Yishuo.

PLAN YOUR CONFIGURATION

Send your cord sample, material, cutting length and required tip size to Yishuo.

NINGBO YISHUO MACHINERY AND ELECTRON CO., LTD.

Lloyd Jiang | WhatsApp: +86 130 4549 3235 | lloyd.jiang@nbyishuo.com